

## 8-Outlet Surge Protector with 2 USB Ports (2.1A Shared) - 8 ft. Cord, 1200 Joules, Tel/Modem, Black

MODEL NUMBER: TLP88TUSBB



8-outlet surge protector safeguards your home/office electronics against dangerous surges, spikes and line noise.

### Features

**8-Outlet Surge Protector with USB Safeguards Your Sensitive Electronics** Ideal for your home or office workstation, this Protect It!® 8-outlet surge protector features a surge protection rating of 1200 joules to defend your sensitive electronic components against strong power surges and spikes. Because residential power outlets have three wires—hot line (H), neutral (N) and ground (G)—the TLP88TUSBB protects all three, covering the two protection modes: full normal mode (H-N) and common mode (N-G/H-G).

**NEMA 5-15R Outlets Accept a Wide Range of Electronic Devices** Plug your PC, printer, wireless router, game console, television, sound system or other home/office electronics into eight NEMA 5-15R outlets to protect them against dangerous surges, spikes and line noise. Three outlets are widely spaced to accommodate bulky power transformers without blocking adjacent outlets. Built-in safety covers prevent dust and debris from falling into unused outlets.

**RJ11 Cable Surge Protection Covers All Your Bases** Built-in RJ11 jacks allow connection of telephone, fax and modem equipment. The TLP88TUSBB prevents dangerous “back door” power surges from damaging your data line components.

**2 USB Ports Share 2.1 Amps of Charging Power** This surge protector with 2 USB ports is ideal for keeping your devices at full capacity. Two USB-A ports are available for charging your smartphone, tablet and other USB mobile devices.

**Premium Protection from EMI/RFI Line Noise Helps Your Equipment Perform Better** Various electromagnetic and radio sources found in virtually every home and business can cause disruptive interference on the AC line. Known as EMI (electromagnetic interference) and RFI (radio frequency interference), this line noise is a common cause of performance problems. This surge protector filters out disruptive line noise that can disturb your electronics and inflict hardware damage or data loss. This EMI/RFI filtering also helps your connected components perform better and last longer.

**Includes the Latest Safety Features** The lighted on/off switch provides one-touch control over connected equipment. A green LED confirms your connected equipment is protected.

**Versatile Surge Protector Provides Multiple Installation Options** This surge protector with 8-foot cord and space-saving right-angle NEMA 5-15P plug helps you connect to a wall outlet located behind furniture placed flush against the wall. Keyhole slots incorporated into the bottom panel provide convenient wall or desk mounting options for the black plastic housing.

### Highlights

- 8 NEMA 5-15R outlets distribute AC power to connected home/office equipment
- 1200 joules protect your valuable electronics against dangerous surges and spikes
- 2 USB ports share 2.1A for fast charging of phones, tablets and other mobile devices
- 8 ft. cord with NEMA 5-15P plug allows flexibility in placing devices away from AC outlet
- RJ11 cable connectors offer surge protection to phone/fax/modem equipment

### Applications

- Protect computers, peripherals, home theater equipment and other valuable electronics against AC power surges and spikes
- Filter potentially damaging line noise to improve connected equipment's performance and lifespan
- Safeguard valuable data against corruption stemming from unexpected surges
- Charge smartphones, tablets or other USB devices via USB ports

### Package Includes

- TLP88TUSBB Protect It! 8-Outlet Surge Protector, Black
- Owner's manual



## Specifications

| OVERVIEW                           |  |
|------------------------------------|--|
| UPC Code                           | 037332223579   |
| OUTPUT                             |  |
| Charging Ports / Amps              | (2) 2.1A   |
| Frequency Compatibility            | 50 / 60 Hz   |
| Output (Watts)                     | 1800   |
| Output Receptacles                 | (8) 5-15R  |
| Circuit Breaker (amps)             | 15   |
| Overload Protection                | 15A resettable illuminated combo switch / circuit breaker                          |
| Transformer Accommodation          | (6) Yes  |
| Outlet Orientation                 | Double row of 8 outlets total  |
| Right-Angle Outlets                | Yes  |
| INPUT                              |  |
| Nominal Input Voltage(s) Supported | 120V AC  |
| Recommended Electrical Service     | 120V (110-125V)  |
| Input Cord Gauge Type              | 14 gauge; SJT  |
| Voltage Compatibility (VAC)        | 120  |
| Maximum Surge Amps                 | 35500  |
| Input Plug Type                    | NEMA 5-15P   |
| Input Cord Length (ft.)            | 8  |
| Right-Angle Plug                   | Yes  |
| Input Cord Length (m)              | 2.44   |
| Integrated Cord Clip               | No   |
| USER INTERFACE, ALERTS & CONTROLS  |  |
| Diagnostic LED(s)                  | Yes  |
| Switches                           | Combination AC circuit breaker and 2 position red illuminated on/off power switch  |
| Diagnostic LED Details             | Built-in LED confirms suppressor "protection present" (green) status               |
| SURGE / NOISE SUPPRESSION          |  |
| AC Suppression Joule Rating        | 1200   |
| AC Suppression Response Time       | < 1 ns   |
| Protection Modes                   | Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression |



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

|  |  |
|--|--|
| UL1449 Let Through Rating                                  | 500,500,500  |
| EMI / RFI Filtering  | Yes  |
| Auto Shut-Off  | No   |
| <b>DATALINE SURGE SUPPRESSION</b>                          |  |
| Telephone/DSL Protection                                   | Yes  |
| Telephone/DSL Protection Details                           | 1 line in/2 line out   |
| Cable (Coax) Protection                                    | No   |
| Network (Ethernet) Protection                              | No   |
| <b>PHYSICAL</b>  |  |
| Shipping Dimensions (hwd / in.)                            | 11.02 x 7.09 x 1.50  |
| Shipping Weight (kg)                                       | 0.75   |
| Unit Dimensions (hwd / in.)                                | 9.10 x 3.78 x 1.30   |
| Unit Dimensions (hwd / cm)                                 | 23.11 x 9.60 x 3.30  |
| Material of Construction                                   | Plastic  |
| Integrated Keyhole Mounting Slots                          | Yes  |
| Housing Color  | Black  |
| Receptacle Color   | Black  |
| Color (AC Line Cord)                                       | Black  |
| Color  | Black  |
| Anti-Microbial Protected                                   | No   |
| <b>CERTIFICATIONS</b>                                      |  |
| UL1449 3rd Edition (AC Suppression)                        | UL1449 3rd EDITION   |
| UL1363 (Power Tap)   | UL1363   |
| Canada   | cUL  |
| Approvals  | Exceeds IEEE 587 category A&B specifications   |
| <b>WARRANTY</b>  |  |
| Product Warranty Period (Worldwide)                        | Lifetime limited warranty  |
| Connected Equipment Insurance (U.S., Canada & Puerto Rico) | \$75,000&nbsp;&nbsp;&nbsp;<a class="insuranceLink" href="//www.tripplite.com/support/insurance-policy">Ultimate Lifetime Insurance</a>&nbsp;&nbsp;&nbsp; |

© 2019 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>