



SX950U STANDBY UPS SYSTEM



Offers significant energy savings, battery backup and surge protection.

The CyberPower SX950U uninterruptible power supply (UPS) safeguards a home office PC and other electronics (monitors, printers, scanners, speakers, fax machines, CD/DVD players and iPods) from surges, spikes, sags, brownouts and other power abnormalities. Its composite integrated circuitry offers advanced lightning protection.

A Three-Year Warranty ensures that this UPS has passed our highest quality standards in design, assembly, material or workmanship and further protection is offered by a \$150,000 Connected Equipment Guarantee.

TYPICAL APPLICATIONS

- Desktop Computers
- Personal Electronics

FEATURES

- 950 VA/510 W
- 12 Standard Outlets
- Standby Topology
- Full-time Surge Protection and Battery Backup
- Three-Year Warranty

SPECIFICATIONS

GENERAL	
UPS Topology	Standby
Energy Saving	Yes
ENERGY STAR® Qualified	Yes
INPUT	
Voltage	120 V
Frequency	50/60 Hz +/- 3 Hz
Circuit Breaker	15A
Plug Type	NEMA 5-15P
Cord Length	5
OUTPUT	
VA	950
Watts	510
On Battery Voltage	120 V ± 5%
On Battery Frequency	50/60 Hz ± 1%
On Battery Waveform	Simulated Sine Wave

OUTPUT CONT.	
Outlets - Total	12
Outlet Type	NEMA 5-15R
Outlets - Battery & Surge Protected	6
Outlets - Surge-Only Protect	6
Outlets - Widely Spaced	4
Overload Protection	Circuit Breakers
USB Charging Ports	2 @ 2.4A Shared
BATTERY	
Runtime at Half Load (min)	7.5
Runtime at Full Load (min)	2
Battery Type	Sealed Lead-Acid
Battery Size	12 V/7.2 Ah
Battery Quantity	1
User Replaceable	Field Replacement

SX950U STANDBY UPS SYSTEM



SPECIFICATIONS CONT.

BATTERY CONT.

Typical Recharge Time	8 hours
-----------------------	---------

SURGE PROTECTION & FILTERING

Surge Suppression	890
-------------------	-----

Phone Protection RJ11	No
-----------------------	----

EMI/RFI Filtration	Yes
--------------------	-----

MANAGEMENT & COMMUNICATIONS

LED Indicators	Power On
----------------	----------

Audible Alarms	On Battery, Low Battery, Overload, Fault
----------------	--

PHYSICAL

Dimensions (WxHxD) (in.)	12.2 x 3.1 x 7
--------------------------	----------------

Weight (lbs.)	7.7
---------------	-----

ENVIRONMENTAL

Operating Temperature	32-104°F (0-40°C)
-----------------------	-------------------

Operating Humidity	0-95% (non-condensing)
--------------------	------------------------

CERTIFICATIONS

Safety	UL1778, cUL, FCC DOC Class B, ENERGY STAR (USA), CEC
--------	--

Environmental	RoHS Compliant
---------------	----------------

WARRANTY

Product Warranty	Three-Years Limited
------------------	---------------------

Connected Equipment Guarantee	Lifetime
-------------------------------	----------

CEG Amount	\$150,000
------------	-----------