

RAABE**MATERIAL SAFETY
DATA SHEET**-----
SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

CHEMICAL PRODUCT IDENTIFICATION:

PRODUCT CODE . . . : 20555 644300 .6B
 PRODUCT NAME . . . : Biscuit 4392899
 PRODUCT CLASS . . . : Touch-Up Bottle

MSDS PREPARATION DATE : 02/23/2006

MANUFACTURER IDENTIFICATION:

RAABE COMPANY
 PO BOX 1090

MENOMONEE FALLS WI 53052-1090

CUSTOMER IDENTIFICATION:

Whirlpool Corporation
 P.D.C. Vnd #018130-1
 1900 Whirlpool Drive
 La Porte, IN 46350

EMERGENCY TELEPHONE NUMBERS:

24 HOURS A DAY - CALL CHEMTREC : 800-424-9300
 INTERNATIONAL CALLS TO CHEMTREC : 703-527-3887
 8 AM TO 4:30 PM CENTRAL TIME : 262-255-9500

SECTION 2 - COMPOSITION, INFORMATION ON INGREDIENTS

1 ETHYLBENZENE

CAS# 100-41-4

ETHYLBENZENE

PCT BY WT: .5470 VAPOR PRESSURE: 19.000 MMHG @ 68F LEL 1.20

EXPOSURE LIMIT:

ACGIH TLV-TWA 100 ppm
 ACGIH TLV-STEL 125 ppm
 OSHA PEL-TWA 100 ppm
 OSHA PEL-STEL 125 ppm
 OTHER IARC (2B), CALIFORNIA PROP 65 (Cancer 6/11/2004)

2 TITANIUM DIOXIDE

CAS# 13463-67-7

TITANIUM DIOXIDE

PCT BY WT: 14.0000

EXPOSURE LIMIT:

ACGIH TLV-TWA 10 mg/m3
 ACGIH TLV-STEL NO INFO
 OSHA PEL-TWA 10 mg/m3
 COMPANY N.E.

3 XYLENE

CAS# 1330-20-7

XYLENE

PCT BY WT: 2.0000 VAPOR PRESSURE: 6.600 MMHG @ 68F LEL 1.00

EXPOSURE LIMIT:
 ACGIH TLV-TWA 100 ppm

RAABE CORPORATION

N 92 WI 4701 ANTHONY AVENUE
 MENOMONEE FALLS, WI 53051-1630
 P.O. BOX 1090 MENOMONEE FALLS, WI 53052-1090
 800 966 7580 | 262 255 9500 | FAX 262 255 0684
 WWW.RAABECORP.COM

RAABE COMPANY
MATERIAL SAFETY DATA SHEET

20555 644300 .6B

ACGIH TLV-STEL 150 ppm
 OSHA PEL-TWA 100 ppm
 OSHA PEL-STEL 150 ppm
 COMPANY N.E.
 LD50(ORAL) 4300 mg/kg
 LD50(DERMAL) 1700 mg/kg
 LC50 18892 mg/m3

4 METHYL ETHYL KETONE
 CAS# 78-93-3
 METHYL ETHYL KETONE
 PCT BY WT: 17.0000 VAPOR PRESSURE: 85.000 MMHG @ 68F LEL 1.80
 EXPOSURE LIMIT:
 ACGIH TLV-TWA 200 ppm
 ACGIH TLV-STEL 300 ppm
 OSHA PEL-TWA 200 ppm
 COMPANY N.E.

5 GLYCOL ETHER PM ACETATE
 CAS# 108-65-6
 PROPYLENE GLYCOL METHYL ETHER ACETATE
 PCT BY WT: 15.0000 VAPOR PRESSURE: 3.700 MMHG @ 68F LEL 1.30
 EXPOSURE LIMIT:
 ACGIH TLV-TWA NOT ESTABLISHED
 ACGIH TLV-STEL NOT ESTABLISHED

6 TOLUENE
 CAS# 108-88-3
 TOLUENE
 PCT BY WT: 23.0000 VAPOR PRESSURE: 38.000 MMHG @ 68F LEL 1.40
 EXPOSURE LIMIT:
 ACGIH TLV-TWA 50 ppm
 ACGIH TLV-STEL NO INFO
 OSHA PEL-TWA 50 ppm
 COMPANY N.E.
 OTHER LIMITS:
 Prop 65-Developmental-01/01/91

 This product contains one or more reported carcinogens or suspected
 carcinogens which are noted NTP, IARC, or OSHA-Z in the other limits
 recommended column.

 This substance is classified as a hazardous air pollutant.

RAABE COMPANY
MATERIAL SAFETY DATA SHEET

20555 644300 .6B

SECTION 3 - HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

Harmful if inhaled.
Causes eye irritation.
Causes skin irritation.
Vapors irritating to eyes and respiratory tract.
Flammable liquid and vapor.

EYE:

May cause eye burns.

SKIN:

May cause skin irritation.
Prolonged contact with the skin can cause chemical burns.
Product contains a component which can be absorbed through the skin.
Excessive exposure may cause hemolysis (red blood cell damage) which can impair the blood's ability to transport oxygen.
Material may aggravate an existing dermatitis.

INHALATION:

Exposure to high concentrations of vapors may cause dizziness, breathing difficulty, headaches or respiratory irritation.
Extremely high concentrations may cause drowsiness, staggering, confusion, unconsciousness, coma or death.
Excessive inhalation of vapors can cause nasal and respiratory irritation.
Liquid or vapor may be irritating to skin, eyes, throat or lungs.
Intentional misuse by deliberately concentrating and inhaling the contents of this product can be harmful or fatal.

INGESTION:

Moderately toxic. May cause stomach discomfort, nausea, vomiting, diarrhea, and narcosis.
Aspiration of material into the lungs if swallowed or if vomiting occurs can cause chemical pneumonitis which can be fatal.
May cause nausea, vomiting and diarrhea.

CHRONIC EFFECTS:

Chronic overexposure to a component or components in this material has been found to cause the following effects in laboratory animals:

- Kidney damage
- Eye damage
- Blood damage
- Lung damage
- Liver damage
- Spleen damage
- Anemia
- Brain damage
- Reproductive system damage

Chronic overexposure to a component or components in this product has been suggested as a cause of the following effects in humans:

- Liver damage
- Cardiac abnormalities

RAABE COMPANY
MATERIAL SAFETY DATA SHEET

20555 644300 .6B

Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage. Repeated breathing or skin contact of methyl ethyl ketone may increase the potency of neurotoxins such as hexane if exposures occur at the same time.

Central nervous system depression, shock, coma, visual disturbances, and death. Onset of symptoms may be delayed as long as 30 hours. Rats exposed to titanium dioxide dust at 250 mg/m³ developed lung cancer, however, such exposure levels are not attainable in the workplace with this material.

2-Butoxyethanol causes harm to the fetus in laboratory animal studies. Harm to the fetus occurs only at exposure levels that harm the pregnant animal. The relevance of these findings to humans is uncertain. Product contains toluene which may be harmful to the fetus based on animal studies.

Repeated exposure to toluene has been associated with high frequency hearing loss in laboratory animals. The human consequences of this finding is uncertain.

In April 1996, The International Agency for Research on Cancer (IARC) published Monograph 65 which reclassifies Carbon Black into Group 2B (possibly carcinogenic to humans).

In February 2000 the International Agency for Research on Cancer (IARC) classified ethylbenzene as possibly carcinogenic to humans (Group 2B) on the basis of sufficient evidence for carcinogenicity in experimental animals but inadequate evidence for cancer in humans.

SECTION 4 - FIRST AID MEASURES

EYE CONTACT:

Immediately flush eyes with plenty of water. Get medical attention, if irritation persists.

Flush with large quantities of water for 15 minutes.

SKIN CONTACT:

Wash with soap and water. Get medical attention if irritation develops or persists.

Wash thoroughly with soap and water and seek medical attention if irritation persists. Remove contaminated clothing. Launder contaminated clothing before reuse.

INHALATION:

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.

For inhalation overexposure move person to fresh air. If breathing stops, apply artificial respiration and seek medical attention.

INGESTION:

Since this product may contain materials which can cause lung damage if aspirated into the lungs, the decision whether to induce vomiting or not must be made by a physician after careful consideration of all materials ingested.

Ingestion of large quantities of this material will result in methanol poisoning. In this case treatment should include hemodialysis; the

RAABE COMPANY
MATERIAL SAFETY DATA SHEET

20555 644300 .6B

administration of ethanol to interfere with the metabolism of methanol and the administration of sodium carbonate to correct acidosis.

SECTION 5 - FIRE FIGHTING MEASURES

FIRE AND EXPLOSIVE PROPERTIES OF THE PRODUCT:

Flashpoint	25.0 °F	
Explosion Level	Low (LEL) -	1.0
	High (UEL) -	13.1

EXTINGUISHING MEDIA:

Use Dry Chemical, Carbon Dioxide or Chemical Foam.

FIRE-FIGHTING PROCEDURES AND EQUIPMENT:

Keep containers tightly closed. Isolate from heat, sparks, and open flame. Closed containers may explode when exposed to extreme heat.

Product vapors are heavier than air and may travel a long distance to a source of ignition and flash back.

Full protective equipment including self-contained breathing apparatus to avoid inhalation of vapors should be used.

Water spray should not be used except to keep down vapors or cool closed containers to prevent build-up of pressure. If water is used, fog nozzles are preferred.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

CLEAN-UP AND CONTAINMENT:

Remove all sources of ignition. Avoid heat, sparks, flames and anything which could cause fire.

Ventilate area of spill and adjacent low lying areas. Avoid breathing solvent vapors. Remove with inert absorbent materials and non-sparking tools.

Use water spray to disperse vapors. Minimize breathing gases, vapor, fumes or decomposition products. Use self-contained breathing apparatus with full face piece operated in positive pressure mode as needed.

SECTION 7 - HANDLING AND STORAGE

HANDLING:

Wash hands thoroughly after handling.

This product contains chemical(s) which are listed on California's proposition 65 list. If the product is to be sold or used in California a clear and reasonable warning must be provided such as:

Warning! This product contains a chemical or chemicals known to the State of California to cause cancer.

STORAGE:

Store in a cool dry area with ventilation suitable for storing materials shown in section 2.

Keep away from heat, sparks and flame.

Store in a cool place away from direct sunlight or any source of ignition. Do not store at temperatures above 120 degrees F.

RAABE COMPANY
MATERIAL SAFETY DATA SHEET

20555 644300 .6B

SECTION 8 - EXPOSURE CONTROLS, PERSONAL PROTECTION

ENGINEERING CONTROLS:

Sufficient ventilation, in volume and pattern, should be provided to keep air contamination below current applicable OSHA permissible exposure limit or ACGIH's TLV limit.

RESPIRATORY PROTECTION:

If workplace exposure limits are exceeded for any component (see section 2 for hazardous components and exposure limits), a NIOSH/OSHA approved respirator suitable for components listed is recommended.

SKIN PROTECTION:

Chemical resistant plastic or rubber gloves recommended for prolonged or repeated contact.

EYE PROTECTION:

Chemical goggles with side shields or face shield recommended if contact with the eyes is likely.

OTHER PROTECTIVE EQUIPMENT:

Appropriate impervious clothing is recommended if prolonged or repeated contact is likely.

HYGIENIC PRACTICES:

Wash hands before eating or smoking. Smoke in designated areas only.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Vapor Pressure	85.00	mm Hg @ 20 C
Vapor Density	3.70	
Boiling Range	Lower - 175.0	°F
	Higher - 302.0	°F
Specific Gravity	1.066	
Formula Weight per Volume	5.224	8.8721 LB/GL
VOC (Calculated, LB/GAL)	625.99	
VOC (Calculated, GM/L)	59.0278	
Percent Volatile by Weight	71.9574	
Percent Volatile by Volume	4.600	(n-Butyl Acetate = 1)
Evaporation Rate	-N/A	
Viscosity		

SECTION 10 - STABILITY AND REACTIVITY

CONDITIONS TO AVOID:

Avoid contact with heat, sparks, and open flame.

INCOMPATIBILITIES:

Strong oxidizing agents.

DECOMPOSITION:

Thermal decomposition may produce carbon dioxide, carbon monoxide, and unidentifiable organic materials.

POLYMERIZATION:

No hazardous polymerization will occur under normal conditions.

STABILITY:

RAABE COMPANY
MATERIAL SAFETY DATA SHEET

20555 644300 .6B

The product is stable under normal storage conditions.

SECTION 11 - TOXICOLOGICAL INFORMATION

No specific information is available. Please refer to Section 2 and 3 for available information on exposure limits and hazards identification.

SECTION 12 - ECOLOGICAL INFORMATION

No specific ecological information is available for this product.

SECTION 13 - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL:

Place in closed containers. Dispose of product in accordance with local, county, state, and federal regulations.

SECTION 14 - TRANSPORT INFORMATION

Ground shipment of limited or excepted quantities of aerosols or liquid paint in containers of 1 quart or less:

CONSUMER COMMODITY, ORM-D
Ground shipment of liquid paint in containers more than 1 quart:
PAINT, FLAMMABLE LIQUID, UN1263, CLASS 3, GROUP II
(Regulatory sources: DOT 49CFR 172.101)

Air shipment of limited or excepted quantities of aerosols or liquid paint in containers of 1 quart or less:

CONSUMER COMMODITY, ID 8000, CLASS 9 MISCELLANEOUS LABEL
(Regulatory sources: ATAI Quantity Exemptions - Table 2.8.4, 2.7.A, 2.7.5, Packaging Instruction: 910)

OR
AEROSOLS, FLAMMABLE, UN1950, CLASS 2.1 LABEL
(Regulatory sources: ATAI Quantity Exemptions - Table 2.8.1, 2.8.4, Packaging Instruction: Y203)

SECTION 15 - REGULATORY INFORMATION

SARA 313 INFORMATION:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

ETHYLBENZENE
CAS# 100-41-4 PCT BY WT: .5470

XYLENE
CAS# 1330-20-7 PCT BY WT: 2.4960

RAABE COMPANY
MATERIAL SAFETY DATA SHEET

20555 644300 .6B

TOLUENE

CAS# 108-88-3, PCT BY WT: 22.6000

FEDERAL REGULATIONS:

TOXIC SUBSTANCES CONTROL ACT: The chemical substances in this product are listed on the TSCA Section 8 inventory.

STATE REGULATIONS:

This product contains chemical(s) which are listed on California's proposition 65 list. If the product is to be sold or used in California a clear and reasonable warning must be provided such as:

Warning! This product contains a chemical or chemicals known to the State of California to cause cancer.

Warning! This product contains a chemical or chemicals known to the State of California to cause birth defects or other reproductive harm.

NEW JERSEY RIGHT-TO-KNOW

The following non-hazardous ingredients are among the top five components in this product

CHEMICAL NAME	CAS NUMBER
---------------	------------

PENNSYLVANIA RIGHT-TO-KNOW

The following non-hazardous ingredients are present in the product at greater than 3 %

CHEMICAL NAME	CAS NUMBER
---------------	------------

Cellulose Acetate Butyrate	9004-36-8
Acrylic Polymer	Not Listed

INTERNATIONAL REGULATIONS:

CANADA: The chemical substances in this product are listed on the Canadian Domestic Substances List.

SECTION 16 - OTHER INFORMATION

The information contained on this MSDS is believed to be reliable and accurate. Due to the changing nature of government information, it is impossible to guarantee the accuracy of the information contained herein. Since the conditions of handling and use are beyond our control, we make no guarantee of results and assume no liability for damages incurred by the use of this material. This information should not be regarded as legal advice or regulation. It is the responsibility of the user to comply with all Federal, State, and Local laws and regulations. For questions relating to specific aspects of the requirements and regulations consult the proper regulatory agency.

HMIS RATINGS:

HEALTH: 2* FLAMMABILITY: 3 REACTIVITY: 0 PERSONAL PROTECTION: B