

## 16-4C

# PRODUCT SPECIFICATIONS

<b>Description:</b>	16/4 High Strand Audio Cable, unshielded with an Overall PVC Jacket
<b>Ratings/Approvals:</b>	NEC Article 800, UL Subject 444, Type CM/CL3, C(ETL)US, RoHS Compliant
<b>Applications:</b>	Intercom Systems, Security Systems, Sound and Audio, Background Music, and Power-Limited Control Circuits. Indoor Applications

---

---

## CONSTRUCTION

Conductor:	16 AWG Bare Copper (OF)
Stranding:	65 x 34
Insulation Material:	Polyvinyl Chloride
Insulation Thickness:	0.012 in. (0.304 mm.) Nominal
Number of Conductors or Pairs:	4 Conductor
Shield:	N/A
Drain:	N/A
Jacket Material:	Polyvinyl Chloride
Jacket Thickness:	0.018 in. (0.457 mm.) Nominal
Overall Cable Diameter:	0.238 in. (6.045 mm.) Nominal
Approx Cable Weight /1,000 ft.:	50 lbs.

---

---

## ELECTRICAL & PHYSICAL PROPERTIES

Operative Voltage:	300 V, RMS
Insulation Colors:	Black, Red, White, Green
Temperature Rating:	-20°C to +75°C