



CTC Laboratories, Inc.

1F, Block 2 & 2F, Block 1, Jiaquan Building, Guanlan High-tech Park, LongHua District, Shenzhen, GuangDong, PRC
Tel : +86-755-27521059
Fax: +86-755-27521011

Report No.: CTC20201286S02

Page 1 of 9

Material Safety Data Sheet

Product Name.....: Lithium Battery

Trademark.....: --

Main Model.....: CR2025

Applicant.....: Dongguan King Power Digital Technology Co.,Ltd

Address of Applicant.....: No.7,Buliding D, Longjiang 2nd Road, Qingxi Town, Dongguan City, Guangdong Province, P.R.China

Manufacturer.....: Heyuan dongrun new energy technology co. LTD.

Address of Manufacturer.....: The second floor, north of longling road, longling industrial park, longling industrial park, yuancheng district, heyuan city.

Nominal Voltage.....: 3.0V

Typical Capacity.....: 150mAh ,0.450Wh

Weight.....: 2.4g Max

Shape and Physical Dimension(mm).....: Button, H : 2.5mm Φ: 20mm

Report Reference No.....: CTC20201286S02

Date of Issue.....: Sep.01, 2020

Testing Laboratory.....: CTC Laboratories, Inc.

Address.....: 1F, Block 2 & 2F, Block 1, Jiaquan Building, Guanlan High-tech Park, LongHua District, Shenzhen, GuangDong, PRC

Tested by (name + signature).....: Paul Chen *Paul chen*

Compiled by (name + signature).....: Max Chen *Max chen*

Approved by (name + signature).....: Totti Zhao *Totti Zhao*



CTC Laboratories, Inc.
1F, Block 2 & 2F, Block 1, Jiaquan Building, Guanlan High-tech Park, LongHua District, Shenzhen, GuangDong, PRC
Tel.: (86)755-27521059 Fax.: (86)755-27521011 Http://www.sz-ctc.org.cn



For anti-fake verification, please visit the official website of Certification and Accreditation Administration of the People's Republic of China : yz.cnca.cn



Section 1. Chemical Product and Company Identification	
Products Name	Lithium Battery
Model	CR2025
Manufacture Name	Dongguan King Power Digital Technology Co.,Ltd
Address	No.7,Buliding D, Longjiang 2nd Road, Qingxi Town, Dongguan City, Guangdong Province, P.R.China
Emergency Telephone No.	18576741421
Fax	--
E-mail address	renqiqi@bldpower.cn
Item Number	CTC20201286S02
Date Prepared	Sep.01, 2020
Referenced documents	ISO 11014:2009 Safety data sheet for chemical products

Section 2. Hazards Identification	
Preparation Hazards and Classification	When the battery is In extreme pressure deformation, high-temperature environment, overload, short-circuit condition, or disassemble the battery, an explosion of fire and chemical burn hazards may occur.
Apperance, Color and Odor	Solid object with no odor,silver.
Primary Route(s) of Exposure	These chemicals are contained in a sealed aluminium enclosure. Risk of exposure occurs only if the cell is mechanically, thermally or electrically abused to the point of compromising the enclosure. If this occurs, exposure to the electrolyte solution contained within can occur by inhalation, ingestion, eye contact and skin contact.
Potential Health Effects	<p>ACUTE (short term): See section 8 for exposure controls In the event that this battery has been ruptured, the electrolyte solution contained within the battery would be corrosive and can cause burns.</p> <p>Inhalation: A battery volatilizes no gas unless it was damaged. Damaged battery will volatilize little gas that may stimulate the respiratory tract or cause an anaphylaxis in serious condition.</p> <p>Ingestion: Swallowing battery will be damaged to the respiratory tract and cause chemical burns to the stomach; in serious conditions it will cause permanent damage.</p> <p>Skin: In normal condition, contact between the battery and skin will not cause any harms. Contact with a damaged battery may cause skin allergies or chemical burns.</p> <p>Eye: In normal condition, contact between the battery and eyes will not cause any</p>



	harms. However, the gas volatilize from a damaged battery may be harmful to eyes.
Medical Conditions Aggravated by Exposure	Not applicable.
Reported as Carcinogen	Not applicable.

Section 3. Composition/Information on Ingredients

Chemical Name	Percent of Content	CAS No.
Manganese Dioxide	30%	1313-13-9
Propylene Carbonate	6%	108-32-7
Lithium Perchlorate	1.5%	7791-03-9
Lithium or Lithium Alloy	5%	7439-93-2
Graphite	4%	7782-42-5
Stainless steel	53.5%	12597-68-1

Note: CAS No. = Chemical Abstract Service Registry Number.

Section 4. First Aid Measures

Skin Contact	Not anticipated. If the battery is leaking and the contained material contacts the skin, flush with copious amounts of clear water for at least 15 minutes.
Eye Contact	Not anticipated. If the battery is leaking and the contained material contacts eyes, flush with copious amounts of clear water for at least 15 minutes. Get medical attention at once.
Inhalation	Not anticipated. If the battery is leaking, remove to fresh air. If irritation persists, consult a physician.
Ingestion	Not anticipated. If the battery is leaking and the contained material is ingested, rinse mouth and surrounding area with clear water at once. Consult a physician immediately for treatment.

Section 5. Fire Fighting Measures

Unusual Fire and	Battery may explode or leak potentially hazardous vapors subject to: exposed to
------------------	---------------------------------------------------------------------------------

CTC Laboratories, Inc.

1F, Block 2 & 2F, Block 1, Jiaquan Building, Guanlan High-tech Park, LongHua District, Shenzhen, Guangdong, PRC
Tel.: (86)755-27521059 Fax.: (86)755-27521011 Http://www.sz-ctc.org.cn



Explosion Hazards	excessive heat (above the maximum rated temperature as specified by the manufacturer) or fire, over-charged, short circuit, punctured and crushed.
Hazardous Combustion Products	Fire, excessive heat, or over voltage conditions may produce hazardous decomposition products. Damaged batteries can result in rapid heating and the release of flammable vapors.
Extinguishing Media	Dry chemical type extinguishers are the most effective means to extinguish a battery fire. ACO ₂ extinguisher will also work effectively.
Fire Fighting Procedures	Use a positive pressure self-contained breathing apparatus if batteries are involved in a fire. Full protective clothing is necessary. During water application, caution is advised as burning pieces of flammable particles may be ejected from the fire.

Section 6. Accidental Release Measures

The material contained within the battery would only be released under abusive conditions. In the event of battery rupture and leakage, collect all the released materials that are not hot or burning in an appropriate waste disposal container while wearing proper protective clothing and ventilate the area. Placed in approved container and disposed according to the local regulations.

CTC Laboratories, Inc.

1F, Block 2 & 2F, Block 1, Jiaquan Building, Guanlan High-tech Park, LongHua District, Shenzhen, GuangDong, PRC
Tel.: (86)755-27521059 Fax.: (86)755-27521011 Http://www.sz-ctc.org.cn



Section 7. Handling and Storage	
Handling	<ol style="list-style-type: none">1. Batteries are designed to be recharged. However, improperly charging a battery may cause the battery to flame. When charging the battery, use dedicated chargers and follow the specified conditions.2. Never disassemble or modify a battery.3. Do not immerse, throw, and wet a battery in water.4. Should a battery unintentionally be crushed, thus releasing its contents, rubber gloves must be used to handle all battery components. Avoid the inhalation of any vapors that may be emitted.5. Short circuit causes heating. In addition, short circuit reduces the life of the battery and can lead to ignition of surrounding materials. Physical contact with to short-circuited battery can cause skin burn.6. Avoid reversing the battery polarity, which can cause the battery to be damaged or flame.7. In the event of skin or eye exposure to the electrolyte, refer to Section 4, First Aid Measures.
Storage	<ol style="list-style-type: none">1. Batteries should be separated from other materials and stored in a noncombustible, well ventilated, sprinkler-protected structure with sufficient clearance between walls and battery stacks. Do not place batteries near heating equipment, nor expose to direct sunlight for long periods.2. Do not store batteries above 30°C or below -5°C. Store batteries in a cool (about 20±5°C) in a long time, dry and ventilated area that is subject to little temperature change. Elevated temperatures can result in reduced battery cycle life. Battery exposure to temperatures in excess of 60°C will result in the battery venting flammable liquid and gases.3. Keep batteries in original package until use and do not jumble them.

Section 8. Exposure Controls/Personal Protection	
Engineering Controls	Keep away from heat and open flame.
Ventilation	Not necessary under conditions of normal use. In case of abuse, use adequate mechanical ventilation (local exhaust) for the battery that vent gas or fumes.
Respiratory Protection	Not necessary under conditions of normal use. If battery is burning, leave the area immediately. During fire fighting, fireman should use self-contained breathing, full-face respiratory equipment. Fires may be fought but only from safe fire fighting distance, evacuate all persons from the area of fire immediately.
Eye Protection	Not necessary under conditions of normal use. Use safety glasses with side shields if handling a leaking or ruptured battery.
Body Protection	Not necessary under conditions of normal use. Use rubber apron and protective working in case of handling a leaking of ruptured battery.
Protective Gloves	Not necessary under conditions of normal use. Use chemical resistant rubber gloves if handling a leaking or ruptured battery.
Others	Use good chemical hygiene practice. Wash hands thoroughly after cleaning-up a battery spill caused by leaking battery. No eating, drinking, or smoking in battery storage area.

Section 9. Physical and Chemical Properties	
State	Form: Solid, Colour: Black, Odour: Monotony
pH	N/A
Melting point/freezing point	N/A
Boiling Point, initial boiling point and Boiling range	N/A
Flash Point	N/A
Upper/lower flammability or explosive limits	N/A
Vapor Pressure	N/A
Vapor Density: (Air = 1)	N/A
Density/relative density	N/A
Solubility in Water	insoluble
n-octanol/water partition coefficient	N/A
Auto-ignition temperature	130 degree
Decomposition temperature	N/A
Evaporation rate	N/A
Flammability (soil, gas)	N/A
Viscosity	N/A



Section 10. Stability and Reactivity	
Stability	Stable
Conditions to Avoid	Do not heat, throw into fire, disassemble, short circuit, immerse in water or overcharge, etc.
Incompatibility	None during normal operation. Avoid exposure heat, open flame and corrosives.
Hazardous Polymerization	Will not occur
Hazardous Decomposition Products	The battery may release irritative gas once the electrolyte leakage.

Section 11. Toxicological Information	
The battery does not elicit toxicological properties during routine handling and use. If the battery is opened through misuse or damage, discard immediately. Internal components of cell are irritant and sensitization.	
Irritancy	The electrolytes contained in this battery can irritate eyes with any contact. Prolonged contact with the skin or mucous membranes may cause irritation.
Sensitization	No information is available.
Teratogenicity	No information is available.
Carcinogenicity	No information is available.
Mutagenicity	No information is available.
Reproductive toxicity	No information is available.
Acute Toxicity:	
7440-50-8	Oral (rat) LD50:5800 mg/kg.
Others	No information is available.

Section 12. Ecological Information	
1. When properly used and disposed, the battery does not present environmental hazard. 2. The battery does not contain mercury, cadmium, or lead. 3. Do not let internal components enter marine environment. Avoid releasing to waterways, wastewater or ground water.	

CTC Laboratories, Inc.
1F, Block 2 & 2F, Block 1, Jiaquan Building, Guanlan High-tech Park, LongHua District, Shenzhen, GuangDong, PRC
Tel.: (86)755-27521059 Fax.: (86)755-27521011 Http://www.sz-ctc.org.cn



Section 13. Disposal Considerations

1. Disposal of the battery should be performed by permitted, professional disposal firms knowledgeable in Federal, State or Local requirements of hazardous waste treatment and hazardous waste transportation.
2. The battery should be completely discharged prior to disposal and/or the terminals taped or capped to prevent short circuit. When completely discharged it is not considered hazardous.
3. The battery contains recyclable materials. Recycling options available in your local area should be considered when disposing of this product, through licensed waste carrier.

Section 14. Transport Information

This report applies to by sea, by air and by land; The lithium ion or lithium polymer cells or batteries must be of a design type proved to meet the testing requirements of the Manual of test and criteria, Part III, subsection 38.3;

The lithium ion or lithium polymer cells and batteries according to PACKING INSTRUCTION Section II of PI 965-967 of the IATA Dangerous Goods regulations 61st Edition may be transported.

Li-Polymer Battery was protected so as to prevent short circuits. This includes protection against contact with conductive materials within the same packaging that could lead to short circuit;

Cell and battery offered for transport must be packed in inner packaging that completely encloses the cell or battery; to provide protection from damage or compression to the batteries, the inner packaging's must be placed in a strong rigid outer packaging;

The packaging shall be adequate to avoid mechanical damage during transport, handling and stacking. The materials and pack design shall be chosen so as to prevent the development of unintentional electrical conduction, corrosion of the terminals and ingress of moisture. The package must be handled with care and that a flammability hazard exists if the package is damaged;

Each package must be labeled with a Lithium Battery handling label or in addition to the Class 9 hazard label. With regard to transport, the following regulations are cited and considered:

- The International Civil Aviation Organization (ICAO) Technical Instructions.
- The International Air transport Association (IATA) Dangerous Goods Regulations.

UN number of lithium battery: UN3480 or UN3481;

UN Proper shipping name/Description (technical name): Lithium ion batteries or Lithium ion batteries contained in equipment or Lithium ion batteries packed with equipment;

UN Classification (Transport hazard class): Non dangerous;

Marine pollutant(Y/N): N;

- The International Maritime Dangerous Goods (IMDG) Code.

For lithium-ion batteries by sea, provided that packaging is strong and prevent the products from short-circuit.

UN number of lithium battery: UN3480 or UN3481;

UN Proper shipping name/Description (technical name): Lithium ion batteries or Lithium ion batteries

CTC Laboratories, Inc.

1F, Block 2 & 2F, Block 1, Jiaquan Building, Guanlan High-tech Park, LongHua District, Shenzhen, Guangdong, PRC
Tel.: (86)755-27521059 Fax.: (86)755-27521011 Http://www.sz-ctc.org.cn



contained in equipment or Lithium ion batteries packed with equipment;
UN Classification (Transport hazard class): Non dangerous;
Marine pollutant(Y/N): Y;
Special Provision: International maritime dangerous goods code (IMDG) 188, 230, 310, 348, 957;
- The US Hazardous Materials Regulation (HMR) pursuant to a final rule issued by RSPA.
- The Office of Hazardous Materials Safety within the US Department of Transportations' (DOT) Research and Special Programs Administration (RSPA).

Section 15. Regulatory Information

OSHA hazard communication standard (29 CFR 1910.1200): Non-hazardous.
China: This MSDS in accordance with GB/T18287-2013 General specification of lithium-ion cells and batteries for mobile phone.
USA: This MSDS meets/exceeds OSHA requirements.
International: This MSDS conforms to European Union (EU), the International Standards Organization (ISO) and the International Labour Organization (ILO).
UL certification: The Future Power batteries are registered by Underwriters Laboratories, Northbrook.
PS.1. When large amount of batteries are transported by ship, vehicle and railroad, avoid high temperature and dew condensation.
PS.2. Avoid transportation which may cause damage of package.

Section 16. Other Information

The information above is believed to be accurate and represents the best information currently available to us. however, CTC makes no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. users should make their own investigations to determine the suitability of the information for their particular purposes. although reasonable precautions have been taken in the preparation of the data contained herein, it is offered solely for your information, consideration and investigation. this material safety data sheet provides guidelines for the safe handling and use of this product; it does not and cannot advise on all possible situations, therefore, your specific use of this product should be evaluated to determine if additional precautions are required.

The data/information contained herein has been reviewed and approved for general release on the basis that this document contains no export controlled information.

==== End of report =====

SDS REPORT

Client Name : Dongguan King Power Digital Technology Co., Ltd

Address : No.7, Building D, Longjiang 2nd Road, Qingxi Town,
Dongguan City, Guangdong Province, P.R.China

Product Name : Li-ion Battery

Date : Jan. 14, 2020

Shenzhen Anbotek Compliance Laboratory Limited



SAFETY DATA SHEET**According to HCS-2012 APPENDIX D TO §1910.1200 (Version: 1.0/EN)****1. Identification**

Sample name: Li-ion Battery

Battery model: 18500

Rating: Nominal Voltage: 7.4V
Rated Capacity: 1600mAh
Weight: 73.55g

Manufacture: Dongguan King Power Digital Technology Co., Ltd

Address: No.7, Building D, Longjiang 2nd Road, Qingxi Town, Dongguan City, Guangdong Province, P.R.China

Factory: Dongguan King Power Digital Technology Co., Ltd

Address: No.7, Building D, Longjiang 2nd Road, Qingxi Town, Dongguan City, Guangdong Province, P.R.China

Telephone no: 0769-82664891

E-mail: renqiqi@bldpower.cn

Date of received: Jan. 13, 2020

Date of report: Jan. 14, 2020

Written by: *Jely Yang*

* Approved * Approved by:

Jeff Zhu


2. Hazard(s) identification

Classification

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200) This product is an article which is a sealed battery and as such does not require an MSDS per the OSHA hazard communication standard unless ruptured. The hazards indicated are for a ruptured battery.

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Skin sensitization	Category 1
Carcinogenicity	Category 2
Specific target organ toxicity (repeated exposure)	Category 1

GHS Label elements, including precautionary statements Emergency Overview

Signal word	Danger	
Hazard Statements	Causes skin irritation Causes serious eye irritation May cause an allergic skin reaction Suspected of causing cancer Causes damage to organs through prolonged or repeated exposures	
		
This product is an article which contains a chemical substance. Safety information is given for exposure to the article as sold. Intended use of the product should not result in exposure to the chemical substance. This is a battery. In case of rupture: the above hazards exist.		
Appearance Silver	Physical State Solid containing liquid	Odor None

Precautionary Statements - Prevention

- Obtain special instructions before use
- Do not handle until all safety precautions have been read and understood
- Use personal protective equipment as required
- Wash face, hands and any exposed skin thoroughly after handling
- Contaminated work clothing should not be allowed out of the workplace
- Wear protective gloves
- Do not breathe dust/fume/gas/mist/vapors/spray
- Do not eat, drink or smoke when using this product
- Wear eye/face protection

Code: AB-BAT-61-a

Shenzhen Anbotek Compliance Laboratory Limited

Address: East of 4/F., Building A, Hourui No.3 Industrial Zone, Xixiang Street, Bao'an District, Shenzhen, Guangdong, China

Tel:(86)755-26066126 Fax:(86)755-26066021 Email:service@anbotek.com



Hotline
400-003-0500

www.anbotek.com

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

Specific treatment (see supplemental first aid instructions on this label)

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

Skin

IF ON SKIN: Wash with plenty of soap and water

Take off contaminated clothing and wash before reuse

If skin irritation or rash occurs: Get medical advice/attention

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Unknown Toxicity

37.3% of the mixture consists of ingredient(s) of unknown toxicity

Other information

Very toxic to aquatic life with long lasting effects

Repeated or prolonged skin contact may cause allergic reactions with susceptible persons

Interactions with Other Chemicals

No information available.

3. Composition/Information on Ingredients

Chemical Name	Percent of Content	CAS No.
Lithium cobalt oxide	29	12190-79-3
Graphite	17	7782-42-5
Carbon black	4	1333-86-4
Carbonate, methyl ethyl	10	623-53-0
Phosphate(1-), hexafluoro-, lithium	9	21324-40-3
Copper	16	7440-50-8
Nickel	4	7440-02-0
Aluminum	11	7429-90-5



4. First-Aid Measures

(a) Description of first aid measures

Inhalation: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice / attention if you feel unwell.

Skin contact: Remove contaminated clothes and rinse the skin with plenty of water. Get medical advice / attention if you feel unwell.

Eye contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice / attention if you feel unwell.

Ingestion: Have victim drink 60 to 240 mL (2-8 oz.) of water. and DO NOT induce vomiting. Get medical aid.

(b) Most important symptoms/effects, acute and delayed

Contact with internal components may cause allergic skin sensitization (rash) and irritate eyes, skin, nose, throat, respiratory system. Cobalt and Cobalt compounds are considered to be possible human carcinogen(s).

(c) Immediate medical attention and special treatment

No information available.

5. Fire-Fighting Measures

(a) Extinguishing media

Suitable extinguishing media: Use foam, dry powder or dry sand, CO₂ as appropriate.

Unsuitable extinguishing media: No information available.

(b) Special hazards arising from the chemical

Under fire conditions, batteries may burst and release hazardous decomposition products when exposed to a fire situation. This could result in the release of flammable or corrosive materials. Hazardous combustion products: CO, CO₂, Metal oxides, Irritating fumes.

(c) Special protective equipment and precautions for fire-fighters

Firefighters must wear fire resistant protective equipment and appropriate breathing apparatus. The staff must equip with filter mask (full mask) or isolated breathing apparatus. The staff must wear the clothes which can defend the fire and the toxic gas. Put out the fire in the upwind direction. Remove the container to the open space as soon as possible. Spray water on the containers in the fire place to keep them cool until finish extinguishment.

6. Accidental Release Measures

(a) Personal precautions, protective equipment and emergency procedures

If the Rechargeable Li-ion Battery material is released, remove personnel from area until fumes dissipate. Provide maximum ventilation to clear out hazardous gases. The preferred response is to leave the area, dispose the case after the batteries cool and



vapors dissipate. Provide maximum ventilation. Avoid skin and eye contact or inhalation of vapors.

(b) Environmental Precautions

Prevent material from contaminating soil and from entering sewers or waterways.

(c) Methods and materials for containment and cleaning up

If battery casing is dismantled, small amounts of electrolyte may leak. Collect all released material in a plastic lined container. Dispose off according to the local law and rules. Avoid leached substances to get into the earth, canalization or waters.

7. Handling and Storage**(a) Precautions for safe handling**

Always follow the warning information on the batteries and in the manuals of devices. Only use the recommended battery types. Keep batteries away from children. For devices to be used by children, the battery casing should be protected against unauthorized access. Unpacked batteries shall not lie about in bulk. In case of battery change always replace all batteries by new ones of identical type and brand. Do not swallow batteries. Do not throw batteries into water. Do not throw batteries into fire. Avoid deep discharge. Do not short-circuit batteries. Use recommended charging time and current.

(b) Conditions for safe storage, including any incompatibilities

If the Rechargeable Li-ion Battery is subject to storage for such a long term as more than 3 months, it is recommended to recharge the Rechargeable Li-ion Battery periodically. Operating temperature: Charge: 0°C~45°C. Discharge: -10°C~50°C. And recommended at -10°C~45°C for 1 month storage, at -10~35°C for 3 months storage. The capacity recovery rate in the delivery state (50% capacity of fully charged) after storage is assumed to be 80% or more. The voltage for long time storage shall be 6V~8.4V range. Do not store Rechargeable Li-ion Battery haphazardly in a box or drawer where they may short-circuit each other or be short-circuited by other metal objects. Keep out of reach of children.

8. Handling and Storage**(a) Engineering Controls**

Use local exhaust ventilation or other engineering controls to control sources of dust, mist, fumes and vapor. Keep away from heat and open flame. Store in a cool, dry place.

(b) Personal Protective Equipment

Respiratory Protection: Not necessary under normal conditions. Skin and body

Protection: Not necessary under normal conditions, Wear neoprene or nitrile rubber gloves if handling an open or leaking battery.

Hand protection: Wear neoprene or natural rubber material gloves if handling an open or leaking battery.

Eye Protection: Not necessary under normal conditions, wear safety glasses if handling an open or leaking battery.

(c) Other Protective Equipment

Have a safety shower and eye wash fountain readily available in the immediate work area.

(d) Hygiene Measures

Do not eat, drink, or smoke in work area. Maintain good housekeeping.

9. Physical and Chemical Properties

(a) Appearance	Solid
(b) Odor	Monotony
(c) Odor threshold	Not available.
(d) pH	Not available.
(e) Melting point/freezing point	Not available.
(f) Initial boiling point and boiling range	Not available.
(g) Flash point	Not available.
(h) Evaporation rate	Not available.
(i) Flammability	Not available.
(j) Upper/lower flammability or explosive limits	Not available.
(k) Vapor pressure	Not available.
(l) Vapor density	Not available.
(m) Relative density	Not available.
(n) Solubility(ies)	Not available.
(o) Partition coefficient: n-octanol/water	Not available.
(p) Auto-ignition temperature	130°C
(q) Decomposition temperature	Not available.
(r) Viscosity	Not available.

10. Stability and Reactivity

(a) Reactivity

Stable under recommended storage and handling conditions.

(b) Chemical stability

Stable under normal conditions.

(c) Possibility of hazardous reactions

When heated above 150°C the risk of rupture occurs. Due to special safety construction, rupture implies contrelease of pressure without ignition.



(d) Conditions to avoid

Do not subject Rechargeable Li-ion Battery to mechanical shock. Keep away from open flames, high temperature.

(e) Incompatible materials

Strong oxidizer, strong acid.

(f) Hazardous decomposition products

Under fire conditions, the electrode materials can form carcinogenic nickel and cobalt oxides.

11. Toxicological Information**(a) Information on the likely routes of exposure**

Inhalation: Inhalation of a large number of vapors or fumes released due to heat may cause respiratory.

Ingestion: Ingestion of battery contents may cause mouth, throat and intestinal burns and damage.

Skin contact: Contact with battery electrolyte may cause burns and skin irritation.

Eye contact: Contact with battery electrolyte may cause burns. Eye damage is possible.

Under normal conditions (during charge and discharge) release of ingredients does not occur. If accidental release occurs see information in section 2, and 4. Swallowing of a battery can be harmful. Call the local Poison Control Centre for advice and follow-up.

(b) Information on toxicological characteristics

Acute toxicity: No data available.

Skin corrosion/irritation: The liquid in the battery irritates.

Serious eye damage/irritation: The liquid in the battery irritates.

Respiratory sensitization: The liquid in the battery may cause sensitization to some person.

skin sensitization: The liquid in the battery may cause sensitization to some person.

Carcinogenicity: Cobalt and Cobalt compounds are considered to be possible human carcinogen(s).

Germ Cell Mutagenicity: No data available.

Reproductive Toxicity: No data available.

STOT-Single Exposure: No data available.

STOT-Repeated Exposure: No data available.

Aspiration Hazard: No data available.



12. Ecological Information

(a) Ecotoxicity

Water hazard class 1 (Self-assessment): slightly hazardous for water.

(b) Persistence and Degradability

No information available.

(c) Bioaccumulative potential

No information available.

(d) Mobility in soil

No information available.

(e) Other adverse effects

No information available.

13. Disposal Considerations

(a) Safe handling and methods of disposal

Disposal should be in accordance with applicable regional, national and local laws and regulations. Local regulations may be more stringent than regional or national requirements.

Product disposal recommendation: Observe local, state and federal laws and regulations.

Packaging disposal recommendation: Be aware discarded batteries may cause fire, tape the battery terminals to insulate them. Don't disassembly the battery. Completely discharge containers (no tear drops, no powder rest, scraped carefully). Containers may be recycled or re-used. Observe local, state and federal laws and regulations. The potential effects on the environment and human health of the substances used in batteries and accumulators;

the desirability of not disposing of waste batteries and accumulators as unsorted municipal waste and of participating in their separate collection so as to facilitate treatment and recycling.

14. Transport Information

According to PACKING INSTRUCTION 965 ~ 967 of IATA DGR 60th Edition for transportation, the special provision 188 of IMDG (inc Amdt 38-16). The batteries should be securely packed and protected against short-circuits. Examine whether the package of the containers are integrate and tighten closed before transport. Take in a cargo of them without falling, dropping, and breakage. Prevent collapse of cargo piles. Don't put the goods together with oxidizer and chief food chemicals. The transport vehicle and ship should be cleaned and sterilized before transport. During transport, the vehicle should prevent exposure, rain and high temperature. For stopovers, the

vehicle should be away from fire and heat sources. When transported by sea, the assemble place should keep away from bedroom and kitchen, and isolated from the engine room, power and fire source. Under the condition of Road Transportation, the driver should drive in accordance with regulated route, don't stop over in the residential area and congested area.

(a) UN number

3480&3481

(b) UN Proper shipping name

LITHIUM ION BATTERIES (including lithium ion polymer batteries) or; LITHIUM ION BATTERIES CONTAINED IN EQUIPMENT or LITHIUM ION BATTERIES PACKED WITH EQUIPMENT (including lithium ion polymer batteries)

(c) Transport hazard class(es)

9

(d) Packing Instruction (if applicable)

965 II/ IB, 966 II, 967 II

(e) Marine pollutant (Yes/No)

No

(f) Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code)

No information available.

(g) Special precautions

No information available.

15. Regulatory Information**OSHA hazard communication standard (29 CFR 1910.1200)**

Hazardous**V****Non-hazardous****16. Other Information****(a) Preparation and revision information**

Date of previous revision: Not applicable.

Date of this revision: 2019-01-01

Revision summary: The first New SDS

(b) Abbreviations and acronyms

TSCA: Toxic Substances Control Act, The American chemical inventory.

DSL: Domestic Substances List

EINECS: European Inventory of Existing Commercial chemical Substances

ENCS: apanese Existing and New Chemical Substances

ECL: Existing Chemicals List, the Korean chemical inventory

IECSC: Inventory of existing chemical substances in China.



(c) Disclaimer

Because all of our batteries are defined as "articles", they are exempted from the requirements of the Hazard Communication Standard. The information in this SDS is provided all the relevant data fully and truly. However, the information is provided without any warranty on their absolute extensiveness and accuracy. This SDS was prepared to provide safety preventive measures for the users who have got professional training. The personal user who obtained this SDS should make independent judgment for the applicability of this SDS under special conditions. In these special cases, we do not assume responsibility for the damage.

-- End of report --



Article Information Sheet

Fiche d'information Article

Product name: Li-MnO2 Button Cell

Printing date: 07-Jan-2020 Nom du produit: Li-MnO2 pile bouton

Date d'impression: 07-Jan-2020

Article Information Sheet (AIS)

This Article Information Sheet (AIS) provides relevant battery information to retailers, consumers, OEMs and other users requesting a GHS - compliant SDS. Articles, such as batteries, are exempt from GHS SDS classification criteria. The GHS criteria is not designed or intended to be used to classify the physical, health and environmental hazards of an article. Branded consumer batteries are defined as electro - technical devices. The design, safety, manufacture, and qualification of Energizer branded consumer batteries follow ANSI and IEC battery standards.

1. DOCUMENT INFORMATION

Product name: Li-MnO2 Button Cell
Model: CR2032, CR927, CR1025, CR1130, CR1216, CR1220, CR1225, CR1616, CR1620, CR1632, CR2016, CR2020, CR2025, CR2032, CR2050, C2330, CR2354, CR2430, CR2450, CR2477, CR3032
Issue Date: 07-Jan-2020

2. COMPANY INFORMATION

Company name(China) SHENZHEN WEINENG ELECTRONICS CO.,LTD
Address: 7th floor of A-building, Senyang High-tech Park, Tianliao community, Guangming District, Shenzhen
E-mail: weinengdz@163.com
Telephone: +86-755-27809917

3. ARTICLE INFORMATION

Description	Li-MnO2 Button Cell
Use	Lithium Primary/Metal Batteries
Brand	----

Article Feuille d'information (AIS)

Cette fiche d'information Article (AIS) fournit des informations sur la batterie correspondant aux détaillants, aux consommateurs, aux OEM et aux autres utilisateurs qui demandent un SDS SGH-conforme. Les articles, tels que les piles, sont exemptés de critères de classification SGH SDS. Les critères du SGH ne sont pas conçus ou destinés à être utilisés pour classer les risques physiques, la santé et l'environnement d'un article. batteries de consommation de marque sont définis comme des dispositifs électro-technique. La conception, la sécurité, la fabrication, et la qualification des batteries de consommation de marque Energizer sont conformes aux normes de la batterie ANSI et IEC.

1. DOCUMENT D'INFORMATION

Produit Nom: Li-MnO2 pile bouton
Modèle: CR2032, CR927, CR1025, CR1130, CR1216, CR1220, CR1225, CR1616, CR1620, CR1632, CR2016, CR2020, CR2025, CR2032, CR2050, C2330, CR2354, CR2430, CR2450, CR2477, CR3032
Date d'émission: 07-Jan-2020

2. INFORMATIONS SUR LA SOCIÉTÉ

Nom de l'entreprise SHENZHEN WEINENG ELECTRONICS CO., LTD (Chine)
Adresse: 7ème étage d'un immeuble-, Senyang high-tech Park, communauté Tianliao, District Guangming, Shenzhen
Email: weinengdz@163.com
Téléphone: + 86-755-27809917

Article Information Sheet

Fiche d'information Article

Product name: Li-MnO2 Button Cell

Printing date: 07-Jan-2020 Nom du produit: Li-MnO2 pile bouton

Date d'impression: 07-Jan-2020

4. ARTICLE CONSTRUCTION

IMPORTANT NOTE: The battery should not be opened or burned. Exposure to the ingredients contained within or their combustion products could be harmful.

Chemical name	CAS No.	Concentration%
Manganese Dioxide	1313-13-9	32.8
Lithium	7439-93-2	2.04
Iron	7439-89-6	52.78
Propylene carbonate	108-32-7	4.13
1,3-Dioxolane	646-06-0	4
Lithium perchlorate	7791-03-9	4.25

5. HEALTH AND SAFETY

Ingestion:	Do NOT induce vomiting. Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately.
Inhalation:	Remove to fresh air. If breathing has stopped, give artificial respiration. Get medical attention immediately. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If breathing is difficult, (trained personnel should) give oxygen. Delayed pulmonary edema may occur. Get medical attention immediately if symptoms occur.
Skin contact:	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Immediate medical attention is required. May cause an allergic skin reaction.
Eye contact:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Seek immediate medical attention/advice.
Self-protection of the first	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent

3. ARTICLE D'INFORMATION

La description	Li-MnO2 pile bouton
Utilisation	BATTERIE AUX IONS LITHIUM
Marque	----

4. ARTICLE CONSTRUCTION

REMARQUE IMPORTANTE: La batterie ne doit pas être ouvert ou brûlé. L'exposition aux ingrédients contenus dans leurs produits ou de combustion pourrait être nocif.

Nom chimique	N ° CAS.	Concentration%
Dioxyde de manganèse	1313-13-9	32,8
Lithium	7439-93-2	2.04
Le fer carbonate	7439-89-6	52,78
propylène	108-32-7	4.13
1,3-dioxolane	646-06-0	4
lithium perchlorate	7791-03-9	4.25
Dioxyde de manganèse	1313-13-9	32,8

5. SANTÉ ET SÉCURITÉ

Ingestion:	Ne pas faire vomir. Se rincer la bouche et boire beaucoup d'eau. Ne portez rien à la bouche d'une personne inconsciente. Appeler un centre de contrôle médecin ou de poison immédiatement.
------------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Article Information Sheet

Fiche d'information Article

Product name: Li-MnO2 Button Cell

Printing date: 07-Jan-2020 Nom du produit: Li-MnO2 pile bouton

Date d'impression: 07-Jan-2020

aiders: spread of contamination. Avoid contact with skin, eyes or clothing. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Use personal protective equipment as required. Wear personal protective clothing (see section 8).

6. FIRE HAZARD & FIREFIGHTING

Fire Hazard	Batteries may rupture or leak if involved in a fire.
Extinguishing Media	Use any extinguishing media appropriate for the surrounding area.
Special hazards arising from the chemical	In case of fire where lithium batteries are present, flood area with water or smother with a Class D fire extinguishant appropriate for lithium metal, such as Lith-X. Water may not extinguish burning batteries but will cool the adjacent batteries and control the spread of fire. Burning batteries will burn themselves out. Virtually all fires involving lithium batteries can be controlled by flooding with water. However, the contents of the battery will react with water and form hydrogen gas. In a confined space, hydrogen gas can form an explosive mixture. In this situation, smothering agents are recommended. A smothering agent will extinguish burning lithium batteries.
Precautions for fire-fighters	Emergency Responders should wear self-contained breathing apparatus. Burning lithium manganese dioxide batteries produce toxic and corrosive lithium hydroxide fumes.

7. HANDLING AND STORAGE

Storage	Store in a cool, well ventilated area. Elevated temperatures can result in shortened battery life. In locations that handle large quantities of lithium batteries, such as warehouses, lithium batteries should be isolated from unnecessary combustibles.
---------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Inhalation: À l'air frais. Si la respiration est arrêtée, pratiquer la respiration artificielle. Consulter un médecin immédiatement. Ne pas utiliser le bouche-à-bouche si la victime a ingéré ou inhalé la substance; pratiquer la respiration artificielle à l'aide d'un masque de poche muni d'une valve à une voie ou d'un autre appareil médical approprié. Si la respiration est difficile, (du personnel qualifié devrait) donner de l'oxygène. œdème pulmonaire retardé peut se produire. Consulter un médecin si des symptômes apparaissent.

Contact avec la peau: Laver immédiatement avec du savon et beaucoup d'eau tout en enlevant les vêtements contaminés et les chaussures. Une attention médicale immédiate est nécessaire. Peut provoquer une réaction allergique cutanée.

Lentilles de contact: Rincer immédiatement et abondamment avec de l'eau, y compris sous les paupières, pendant au moins 15 minutes. Gardez l'œil ouvert pendant le rinçage. Ne pas frotter les zones touchées. lentilles de contact Retirer, si elle est présente et facile à faire. Continuer à rincer. Consulter un / des conseils médicaux immédiats.

Auto-protection du secouriste: Veiller à ce que le personnel médical sont au courant de la matière (s) impliqués, prendre des précautions pour se protéger et prévenir la propagation de la contamination. Éviter tout contact avec la peau, les yeux ou les vêtements. Éviter tout contact direct avec la peau. Utilisez barrière pour donner la respiration artificielle bouche-à-bouche. Utiliser un équipement de protection individuel requis. Porter des vêtements de protection individuelle (voir la section 8).

6. RISQUE D'INCENDIE & POMPIERS

Article Information Sheet

Fiche d'information Article

Product name: Li-MnO₂ Button Cell

Printing date: 07-Jan-2020 Nom du produit: Li-MnO₂ pile bouton

Date d'impression: 07-Jan-2020

Handling Avoid mechanical and electrical abuse. Do not short circuit or install incorrectly. Batteries may rupture or vent if disassembled, crushed, recharged or exposed to high temperatures. Install batteries in accordance with equipment instructions.

Spills of Large Quantities Batteries (unpackaged) Notify spill personnel of large spills. Irritating and flammable vapors may be released from leaking or ruptured batteries. Spread batteries apart to stop shorting. Eliminate all ignition sources. Evacuate area and allow vapors to dissipate. Clean-up personnel should wear appropriate PPE to avoid eye and skin contact and inhalation of vapors or fumes. Increase ventilation. Carefully collect batteries and place in appropriate container for disposal. Remove any spilled liquid with absorbent material and contain for disposal.

8. DISPOSAL CONSIDERATIONS

Dispose of used (or excess) batteries in compliance with federal, state/provincial and local regulations. Do not accumulate large quantities of used batteries for disposal as accumulations could cause batteries to short-circuit. Do not incinerate. In countries, such as Canada and the EU, where there are regulations for the collection and recycling of batteries, consumers should dispose of their used batteries into the collection network at municipal depots and retailers. They should not dispose of batteries with household trash.

9. Transport information

The transportation of primary lithium cells and batteries is regulated by the International Civil Aviation Organization, International Air Transport Association, International Maritime Dangerous Goods Code and the US Department of

Risque d'incendie Les piles peuvent se rompre ou fuir si elle est impliquée dans un incendie.

Moyens d'extinction Utilisez tous les moyens d'extinction appropriés pour la région environnante.

Dangers particuliers résultant de la substance chimique En cas d'incendie où des batteries au lithium sont présents, zone inondable avec de l'eau ou avec un ÉTOUFFER approprié incendie Classe d'extinction D pour le métal de lithium, comme Lith-X. L'eau ne peut pas éteindre les piles qui brûlent mais refroidir les batteries adjacentes et contrôler la propagation du feu. Les piles qui brûlent va se brûler. Pratiquement tous les feux impliquant des piles au lithium peuvent être contrôlés par les inondations avec de l'eau. Cependant, le contenu de la batterie réagiront avec l'eau et sous forme d'hydrogène gazeux. Dans un espace confiné, le gaz d'hydrogène peut former un mélange explosif. Dans cette situation, les agents étouffants sont recommandés. Un agent étouffant éteindra la combustion des batteries au lithium.

Précautions à prendre pour les pompiers Équipe d'intervention doivent porter un appareil respiratoire autonome. La combustion des piles de dioxyde de manganèse au lithium produisent toxique et corrosif fumées lithium hydroxyde.

7. MANIPULATION ET STOCKAGE

Article Information Sheet

Fiche d'information Article

Product name: Li-MnO2 Button Cell

Printing date: 07-Jan-2020 Nom du produit: Li-MnO2 pile bouton

Date d'impression: 07-Jan-2020

Transportation. The batteries must meet the following criteria for shipment: 1. Air shipments must meet the requirements listed in Special Provision A45 of the International Air Transport Association Dangerous Goods Regulations. 2. Meet the requirements for the US Department of Transportation listed in 49 CFR 173.185. 3. The transport of primary lithium batteries is prohibited aboard passenger aircraft. Refer to the Federal Register December 15, 2004 (Hazardous Materials; Prohibited on the Transportation of Primary Lithium Batteries and Cells Aboard Passenger Aircraft; Final Rule)

Lithium batteries shipped as "Lithium batteries", "Lithium batteries packed with equipment", or "Lithium batteries contained in equipment" may not be classified as "Dangerous Goods" when shipped in accordance with "special provision A45 of IATA-DGR" or "special provision 188 of IMO-IMDG Code"

(a) UN number	3480&3481			
(b) UN Proper shipping name	LITHIUM ION BATTERIES (including lithium ion polymer batteries) or; LITHIUM ION BATTERIES CONTAINED IN EQUIPMENT or LITHIUM ION BATTERIES PACKED WITH EQUIPMENT (including lithium ion polymer batteries)			
(c) Transport hazard class(es)	9			
(d) Packing group (if applicable)	IA			
(e) Marine pollutant (Yes/No)	No			
(f) Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code)	No information available.			
(g) Special precautions	No information available.			
(h) Organizations governing the transport of lithium batteries	Area	Method	Organization	Special Provision
	U.S.A	Air, Rail, Road, Marine	DOT	49 CFR Section 173.185

Espace de rangement de Conserver dans un endroit frais et bien ventilé. Les températures élevées peuvent entraîner dans la vie de la batterie raccourcie. Dans les endroits qui traitent de grandes quantités de
Les piles au lithium, tels que les entrepôts, les batteries au lithium doivent être isolés à partir de combustibles inutiles.

Manipulation Éviter les abus mécaniques et électriques. Ne pas court-circuiter ou installer correctement. Les piles peuvent se rompre ou de ventilation si elles sont démontées, écrasées, rechargées ou exposé à une forte températures. Installez les piles conformément aux instructions du fabricant.

Déversements de grandes quantités de Batteries (non emballés) Informer le personnel de déversement de grands déversements. Irritant et vapeurs inflammables peuvent être libérés de fuites ou les piles endommagées. piles écarter pour arrêter les courts-circuits. éliminer tous les sources d'allumage. Évacuer la zone et laisser les vapeurs se dissipent. Le personnel de nettoyage devrait porter des EPI appropriés pour éviter les yeux et contact avec la peau et l'inhalation des vapeurs ou fumées. Augmenter la ventilation. batteries cueillent et les placer dans un récipient approprié pour disposition. Retirez tout liquide déversé avec une matière absorbante et contiennent pour l'élimination.

8. CONSIDERATIONS RELATIVES À L'ÉLIMINATION

Jetez les piles usagées (ou excédent) conformément aux règlements fédéraux, provinciaux / provinciaux et locaux. Ne pas accumuler de grandes quantités de piles usagées pour l'élimination comme accumulations pourraient provoquer un court-circuit. Ne pas incinérer. Dans les pays,

Article Information Sheet

Fiche d'information Article

Product name: Li-MnO2 Button Cell

Printing date: 07-Jan-2020 Nom du produit: Li-MnO2 pile bouton

Date d'impression: 07-Jan-2020

10. REGULATORY INFORMATION

(a) Safety, health and environmental regulations specific for the product in question

CAS No.	USA TSCA	EU EINECS	Japan ENCS	Korea ECL	China IECSC	Canada DSL
1313-13-9	Listed	Listed	Not Listed	Listed	Listed	Listed
7439-93-2	Listed	Listed	Listed	Listed	Listed	Listed
7439-89-6	Listed	Listed	Listed	Listed	Listed	Listed
108-32-7	Not Listed	Listed	Not Listed	Not Listed	Not Listed	Not Listed
646-06-0	Not Listed	Not Listed	Listed	Not Listed	Listed	Not Listed
7791-03-9	Not Listed	Not Listed	Not Listed	Not Listed	Not Listed	Not Listed

11. OTHER INFORMATION

TSCA: Toxic Substances Control Act, The American chemical inventory.

DSL Domestic Substances List

EINECS: European Inventory of Existing Commercial chemical Substances

ENCS Japanese Existing and New Chemical Substances

ECL: Existing Chemicals List, the Korean chemical inventory.

IECSC: Inventory of existing chemical substances in China.

Because all of our batteries are defined as "articles", they are exempted from the requirements of the Hazard Communication Standard. The information in this AIS is provided all the relevant data fully and truly. However, the information is provided without any warranty on their absolute extensiveness and accuracy. This AIS was prepared to provide safety preventive measures for the users who have got professional training. The personal user who obtained this AIS should make independent judgment for the applicability of this AIS under special conditions. In these special cases, we do not assume responsibility for the damage.

----- End of the AIS -----

comme le Canada et l'Union européenne, où il existe des règlements pour la collecte et le recyclage des batteries, les consommateurs devraient disposer de leurs piles usagées dans le réseau de collecte dans les dépôts municipaux et les détaillants. Ils ne doivent pas jeter les piles avec les ordures ménagères.

9. Informations de transport

Le transport des piles au lithium primaire et les batteries est réglementé par l'Organisation internationale de l'aviation civile, l'Association internationale du transport aérien, Code maritime international des marchandises dangereuses et le Département américain des Transports. Les batteries doivent répondre aux critères suivants pour l'expédition: 1. les livraisons d'air doivent satisfaire aux exigences énumérées à disposition spéciale A45 de l'Association internationale du transport aérien des marchandises dangereuses Règlement. 2. Répondre aux exigences du ministère américain des Transports répertoriés dans 49 CFR 173,185. 3. Le transport des piles au lithium primaire est interdit à bord des avions de passagers. Reportez-vous au Registre fédéral de 15 Décembre 2004 (matières dangereuses, interdites sur le transport des piles au lithium primaire et cellules Aboard passagers d'avion Règle finale)

Les piles au lithium expédiés comme « batteries au lithium », « Les piles au lithium emballées avec un équipement » ou « piles au lithium contenues dans l'équipement » ne peuvent pas être considérés comme des « marchandises dangereuses » lorsqu'ils sont expédiés conformément à la « disposition A45 spéciale de IATA-DGR » ou " disposition spéciale 188 du code de l'OMI-IMDG »

(A) Numéro ONU 3480 & 3481

(B) l'ONU Nom d'expédition Batteries lithium-ion (y compris les piles de polymère au lithium-ion) ou;
Batteries lithium-ion contenues dans un équipement ou LITHIUM ION batteries emballées avec un équipement (y compris les piles de polymère au

Article Information Sheet

Fiche d'information Article

Product name: Li-MnO2 Button Cell

Printing date: 07-Jan-2020

Nom du produit: Li-MnO2 pile bouton

Date d'impression: 07-Jan-2020

----- End of the AIS -----

lithium-ion)

(C) classe de danger pour le transport (s) 9

(D) des groupes d'emballage (le cas échéant) IA

(E) Polluant marin (Oui / Non) Non

(F) de transport en vrac (selon l'Annexe II de MARPOL 73/78 et au recueil IBC) Pas d'information disponible.

(g) Précautions particulières Pas d'information disponible.

(H) Les organisations régissant le transport des batteries au lithium

Zone	Méthode	Organisation	Provision SPECIALE
Etats-Unis	Aérien, ferroviaire, routier, maritime	POINT	49 CFR Section 173,185

10. INFORMATIONS RÉGLEMENTAIRES

(A) la sécurité, de santé et de l'environnement spécifique pour le produit en question

N ° CAS.	Etats-Unis TSCA	UE Einecs	Japon ENCS	Corée ECL	Chine IECS C	Canada DSL
12190-79-3	Listed	Listed	Listed	Listed	Listed	Listed
7782-42-5	Listed	Listed	Non listé	Listed	Non listé	Listed

Article Information Sheet

Fiche d'information Article

Product name: Li-MnO2 Button Cell

Printing date: 07-Jan-2020 Nom du produit: Li-MnO2 pile bouton

Date d'impression: 07-Jan-2020

21324-40-3	Non listé	Non listé	Listed	Non listé	Liste d	Non listé
7440-50-8	Non listé	Non listé	Listed	Non listé	Liste d	Non listé
7429-90-5	Listed	Listed	Listed	Non listé	Liste d	Listed
7440-02-0	Non listé	Listed	Listed	Listed	Non listé	Non listé
9002-86-2	Listed	Non listé	Listed	Listed	Liste d	Listed

11. LES AUTRES INFORMATIONS

TSCA: Toxic Substances Control Act, l'inventaire chimique américain.

DSL: Liste intérieure

Einecs: Inventaire européen des substances chimiques existantes commerciales

ENCS: Existantes et nouvelles substances chimiques japonaises

ECL: Liste des produits chimiques existants, l'inventaire chimique coréenne.

IECSC: Inventaire des substances chimiques existantes en Chine.

Parce que toutes nos batteries sont définis comme des « articles », ils sont exemptés des exigences de la norme de communication des risques. Les informations contenues dans ce AIS est fourni tous les pleinement et véritablement les données pertinentes. Cependant, les informations sont fournies sans aucune garantie sur leur extensification absolue et la précision. Cet AIS a été préparé à des mesures préventives de sécurité pour les utilisateurs qui ont obtenu la formation professionnelle. L'utilisateur personnel qui a obtenu ce SIA devrait porter un jugement indépendant pour l'applicabilité de cette AIS dans des conditions particulières. Dans ces cas particuliers, nous n'assumons la responsabilité pour les dommages.

----- Fin de l'AIS -----