

STARFRIT

INSTRUCTIONS

SECURIMaxAuto



1. Place the can on a flat horizontal surface.

2. PLACE CAN OPENER HORIZONTALLY ONTO THE CAN. Indicator should align with rim.



3. Turn knob clockwise while maintaining can opener horizontal. Knob will move towards the centre of the can



and will remain there. Always remember to stop turning once can opener has cut rim one complete circle. You will feel the resistance change. Never over-cut by more than 30 mm.



4. Turn knob counterclockwise to release the can opener from the can. The knob will return to its natural position. The can is now opened.



5. Do not pry the lid off with your fingers. Always use the lid lifter provided. Press button to engage lid lifter. Release button to drop lid.

WARNING

If you continue to turn once the can is opened, this may create metal shavings. Dispose of can carefully.

IMPORTANT

a) It is important not to turn the knob counterclockwise and release the can opener if the can opener has not cut the rim one complete circle yet. In case there is a need to suspend the can opening process, simply leave the entire set-up where it is and resume turning knob to continue as required.

b) The can opener is designed to be used on conventional household cylindrical cans, with a diameter between 54 mm and 100 mm, weighing less than 1.5kg.

c) Best for rim height between 2.6mm and 3.1mm.

d) It is important to clean your can opener regularly. Use warm soapy water to clean.

SECURIMaxAuto

Button to engage lid lifter (5)

Bouton de la pince brevetée (5)



Indicator (2)
Indicateur (2)

Patented lid lifter (5)
Pince brevetée (5)



Made in China for / Fabriqué en Chine pour :
LES PROMOTIONS ATLANTIQUES INC.
Longueuil (Québec) J4G 1V6
ATLANTIC PROMOTIONS INC
Mississauga (Ontario) L4Z 2H2
www.starfrit.com