

AT8314

cables

Premium Microphone Cables (XLRF – XLRM)



Features

- **Dual copper outer shields and twin conductive PVC inner shields protect cable signal quality with 100% coverage**
- **Professional Neutrik® connectors ensure superior signal integrity and outstanding strain relief**
- **Heavy-duty PVC jacket stands up to tough use**
- **Heavy-duty 24-gauge stranded copper conductors offer optimal signal transfer**
- **Extra flexibility and low memory for ease of use/storage**

Description

Designed for low-impedance operation, these balanced cables feature heavy-duty construction and professional Neutrik® connectors. To protect signal quality, each conductor has an individual spiral shield inside the molded insulating sheath.

Cable Configurations

AT8314-1.5	XLRF – XLRM balanced microphone cable 1.5' (0.5 m) length
AT8314-3	XLRF – XLRM balanced microphone cable 3' (0.9 m) length
AT8314-6	XLRF – XLRM balanced microphone cable 6' (1.8 m) length
AT8314-10	XLRF – XLRM balanced microphone cable 10' (3.8 m) length
AT8314-15	XLRF – XLRM balanced microphone cable 15' (4.6 m) length
AT8314-20	XLRF – XLRM balanced microphone cable 20' (6.1 m) length
AT8314-20R	90° XLRF – XLRM balanced microphone cable 20' (6.1 m) length
AT8314-25	XLRF – XLRM balanced microphone cable 25' (7.6 m) length
AT8314-30	XLRF – XLRM balanced microphone cable 30' (9.1 m) length
AT8314-50	XLRF – XLRM balanced microphone cable 50' (15.2 m) length
AT8314-100	XLRF – XLRM balanced microphone cable 100' (30.5 m) length



Audio-Technica U.S., Inc., 1221 Commerce Drive, Stow, Ohio 44224
Audio-Technica Limited, Old Lane, Leeds LS11 8AG England
©2010 Audio-Technica U.S., Inc. audio-technica.com

0001-0253-00