



USB-C to HDMI & VGA 4-in-1 Docking Converter with Power Delivery

USB 3.2 Type-C Male to HDMI (4K@30Hz), VGA (1080p@60Hz), USB-A (5 Gbps) and USB-C PD (87 W) Females, Pass-through Charging, Aluminum, Space Gray

Part No.: 130691

EAN-13: 0766623130691 | UPC: 766623130691

USB-C to HDMI and VGA Adapter to connect a laptop, MacBook® or PC to a dual-display setup - including USB-A peripheral and PD charging port

The USB-C to HDMI & VGA 4-in-1 Docking Converter with Power Delivery establishes a fast, simple and convenient link between newer USB Type-C equipped media source (laptop, PC, MacBook®, Chromebook™, computer, tablet, etc.) and existing HDMI and VGA displays (monitors, TVs and projectors). You'll enjoy resolutions up to 4K@30Hz on the HDMI connection, up to 1080p@60Hz on the VGA connection, or up to 1080p@60Hz on each display of a dual-display setup. Create a mini-workstation by adding any USB 3.2 Gen 1 (formerly USB 3.0) peripheral such as a mouse, keyboard, hub, external memory device and more with the integrated USB-A port. This multiport Docking Converter is easy and quick to install. No complicated configuration or setup is required to enhance the functionality of your USB-C device. Its all-inone design achieves a compact, integrated solution that eliminates unnecessary cables, tangles and clutter to keep installations and workspaces neat and orderly.

Up to 87 W charging power with USB-C Power Delivery (PD)

The included USB-C PD port lets you charge your notebook with power up to 87 W while simultaneously charging your other mobile devices, such as smartphones or tablets, through the USB-A port. The Power Delivery function also provides faster charging than standard chargers since it determines the power needs of compatible devices and supplies it at the quickest and safest

manhattan-products.com



rate.

Take your phone to the big screen

Connect any Android 9 and later smartphone that supports video output over USB-C DP Alt Mode to enjoy your apps and media even more. Watch a video on your monitor or flip through the slides of your presentation - all from your phone.

A Multiport Adapter that's made to go where you go

The very compact aluminum housing makes this USB-C to HDMI & VGA Docking Converter the perfect travel companion. With a footprint of only $62 \times 40 \times 15$ mm (2.44 x 1.73 x 0.59 in.), it's small enough to fit in an outer notebook bag pocket, so you can create a mini-workstation for your laptop wherever you're going.

Features:

- Creates a dual-display setup, charges your devices and connects a peripheral
- Up to 4K@30Hz UHD (3840×2160) resolution on HDMI connection
- Up to 1080p@60Hz Full HD (1920×1080) resolution on VGA connection
- Dual-video output with resolutions up to 1080p@60Hz on both displays
- Supports display modes Mirror and Extended Mirror
- One USB 3.2 Gen 1 Type-A port (formerly USB 3.0) with SuperSpeed transfer rates up to 5 Gbps and charging up to 5 W (5 V / 1 A)
- USB-A port to connect mice, keyboards or portable memory devices (and more) or to charge and sync a portable electronic device
- Supports USB Power Delivery (PD) function up to 87 W; requires an external PD charger - available from Manhattan
- Compliant with DisplayPort 1.2 Alternate Mode (DP Alt Mode)
- Compatible with all USB-C DP-Alt-Mode-supported desktops, notebooks and tablets including Apple® MacBook®, Chromebook™, Pixel™ and more
- Sturdy, sleek aluminum housing, great for both desktop and travel
- Built-in, sturdy 15 cm (6 in.) cable
- Fully HDCP 1.4 compliant, backward compatible
- Lets your smartphone work like a desktop PC while also charging it (desktop setup requires devices with Android 9 or above that offer video output over USB-C)
- Plug-and-play installation; Windows®, macOS®, Chrome OS™, iPadOS® and Android™ compatible
- Three-year warranty



manhattan-products.com

Specifications:

Standards and Certifications

- DP 1.2 Alt Mode over USB-C
- USB 3.2 Gen 1
- HDMI 1.4
- HDCP 1.4
- CE
- FCC
- RoHS
- REACH
- UKCA

General

- USB-A port data transfer speed: 5 Gbps
- Bus-powered operation (except charging functions)
- USB-C PD charging: 87.0 W max. (20.0 V at 5.0 A)
- USB-A charging: 5.0 W max. (5.0 V at 1.0 A)

Connections

- One USB-C 24-pin, male
- One USB-C 24-pin, female
- One USB-A 4-pin, female
- One HDMI 19-pin, female

Physical

- Dimensions (L x W x H): 62 x 40 x 15 mm (2.44 x 1.73 x 0.59 in.)
- Net weight: 42 g (1.48 oz.)
- Gross weight: 63 g (2.22 oz.)
- Cable length: 15 cm (6 in.)
- Cable diameter: 34 AWG
- Aluminum housing

Operating Environment

- Operation temperature: 0 45°C (32 113°F)
- Storage temperature: -10 70°C (14 158°F)
- Humidity (noncondensing): 5 90% RH

System Requirements

• Windows 7/8.1/10/11, Chrome OS, macOS, iPadOS or Android

Package Contents

- USB-C to HDMI & VGA 4-in-1 Docking Converter with Power Delivery
- Instructions



manhattan-products.com











