

General

Video Transmission

Technology

Image Sensor

4K+ Ultra HD 12MP CMOS (4640 x

2624)

Video Format

NTSC

Video Compression

H.265/H.264 (Main Stream &

Sub Stream)

Optical

Viewing Angle (Horizontal) 139°

Lens/Lens type

2.8mm F1.6/ Fixed

Video Output

Resolution/Frame rate

4K+/12MP@15fps, 4K/8MP@15fps, 5MP@30fps, 1080p@30fps,

720p@30fps

Effective Pixels

H:4512 x V:2512 (11.3MP)

HDR

Yes

Termination

RJ45

Audio

Microphone/Speaker Yes/Yes

Siren

Yes (Siren sound options

available)

Two-way Talk

Yes

Night Vision

IR Night Vision Range 150 ft (45 m)/ 98 ft (30 m)

Color Night Vision™ Yes

Enhanced Color Night

Vision

Pixel Binning

Special Features

Smart Motion Detection Plus Yes 4 - Person and Vehicle

Detection

Detection Types

Vehicle, Person, Face, Face Mask

& Animal

Package Detection

Supports in App Quick

Messaging

Active Deterrence

Smart Security Lighting

Additional Specifications

Camera Housing Material **Aluminum Alloy**

SD Card Slot Yes*

Power Requirements PoE (Power over Ethernet Class

-802.3af)/12V DC

Yes - package missing or package left behind 1

Recorded Message 1

Yes - Warning Light + Siren + Pre

4.8 x 4.8 x 4.8" / 122 x 122 x 122 mm

-22 °F ~ 140 °F / -30 °C ~ 60 °C

Yes

Yes

Power Consumption (max) 790mA / 9.5W

Camera Dimensions

 $(W \times D \times H)$

1.65 lb / 0.75 kg Camera Weight

Operating Temperature

Humidity

< 95% RH

Environmental Rating

IP67 (Indoor/Outdoor)

MODEL INFORMATION

E910DD-Z

Brown Box

6-95529-05150-5

Package Weight

3.55 lb / 1.6 kg Package Dimensions

6.06 × 6.3 × 5.5" /

 $(W \times D \times H)$

154 × 160 × 140 mm

Package Cube

0.122 ft³ / 0.003 m³

Junction Box

Compatible with

ACJNCD3B (Not included)

PACKAGE CONTENTS

- 4K+ IP Dome Camera
- Mounting Kit (Mounting template, anchors & screws)
- CAT5e Ethernet Cable
- Quick Start Guide

Lorex Corporation

10440 Little Patuxent Parkway, Ste, 300, Columbia, MD 21044, United States

As our product is subject to continuous improvement, Lorex Technology & subsidiaries reserve the right to modify product design, specifications & prices without notice and without incurring any obligation. E&OE.

E910DD Series lorex.com



4K+ Smart Security Lighting IP Wired Dome Camera

Disclaimers:

- 1. Compatible with select Lorex Network Video Recorders HD recorders. For a full list of compatible recorders visit: www.lorex.com/compatibility.
- 2. Color nighttime video typically switches to black & white IR night vision when there is not sufficient ambient light to ensure optimal low-light image quality.
- 3. Stated IR illumination range is based on ideal conditions in typical outdoor nighttime ambient lighting (up to 98 ft/30 m in total darkness). Actual range and image clarity depends on installation location, viewing area and light reflection/absorption.
- 4. For Face Detection to operate, this camera requires a connection to a compatible Lorex Network Video Recorder with smart face detection technology. For a list of compatible recorders please visit: www.lorex.com/compatibility.
- 5. Audio recording is disabled by default. Audio recording without consent is illegal in certain jurisdictions. Lorex Technology does not assume liability for any use of its product that fails to conform with local laws.
- 6. Not intended for submersion in water. Installation in a sheltered location recommended.
- 7. Cable length is dependent on product configuration. See product packaging for details.
- 8. Package Detection is compatible with select Lorex Network Video Recorders. For a full list of compatible recorders visit: www.lorex.com/compatibility.

*A microSD card can be inserted for independent recording. Data can be accessed through the camera using a web browser but will not upload to the NVR or to the cloud for mobile app viewing.

Lorex products are designed for consumer and business use only and not for US federal governments, federally-funded projects or contractors subject to NDAA.