



CP600LCD Intelligent LCD UPS

Offers significant energy savings, battery backup and surge protection.

The CyberPower Intelligent LCD Series CP600LCD uninterruptible power supply (UPS) safeguards PCs and other electronics (monitors, cable/DSL modems, VoIP routers, and home theater devices) from blackouts, brownouts, surges, spikes, sags, and other power abnormalities.

PowerPanel® Personal Edition UPS Management software automatically closes computer files and safely shuts down the system in case of a power outage. This UPS system is also ENERGY STAR® qualified.

A Three-Year Warranty ensures that this UPS has passed our highest quality standards in design, assembly, material or workmanship and further protection is offered by a \$175,000 Connected Equipment Guarantee.

Typical Applications

- Desktop Computers
- Home Networking/VoIP
- Personal Electronics
- Home Theater Device

Features

- 600VA / 340W
- Standby Topology
- Multifunction LCD Screen
- ENERGY STAR® Qualified
- Full-time Surge Protection and Battery Backup
- Desktop Form Factor
- RJ11 / RJ45 Protection
- 8 Outlets / USB Port
- PowerPanel® Personal Edition
- 3-Year Warranty

CP600LCD Intelligent LCD UPS

Offers significant energy savings, battery backup and surge protection.

GENERAL	
UPS Topology	Standby
ENERGY STAR® Qualified	Yes
INPUT	
Voltage	100Vac - 140Vac
Frequency	57Hz - 63Hz
Plug Type	NEMA 5-15P
Plug Style	Right Angle
Cord Length	6'
OUTPUT	
VA	600
Watts	340
Automatic Voltage Regulation	No
On Battery Voltage	120Vac ± 5%
On Battery Frequency	60Hz ± 1%
On Battery Waveform	Simulated Sine Wave
Outlets - Total	8
Outlet Type	NEMA 5-15R
Outlets - Battery & Surge Protected	4
Outlets - Surge-Only Protected	4
Outlets - Widely Spaced	4
Overload Protection	Internal circuitry limiting / circuit breaker
Transfer Time	4ms
BATTERY	
Runtime at Half Load (min)	9
Runtime at Full Load (min)	2
Battery Type	Sealed Lead-Acid
Battery Size	12V/7AH
Replacement Battery	RB1270
Battery Quantity	1
User Replaceable	Yes
Typical Recharge Time	8 Hours
SURGE PROTECTION & FILTERING	
Surge Suppression	1,030 Joules
Phone RJ11 / Ethernet RJ45	1-In, 1-Out (Combo)

MANAGEMENT & COMMUNICATIONS	
Multifunction LCD Panel	Displays: Current/Load Level, Runtime, Battery Level, Input Voltage, Output Voltage, Battery In Use, Overload, Silent Mode, Normal Mode
USB Port	Yes
HID Compliant USB Port	Yes
Management Cable	USB Cable
LED Indicators	Power On, Wiring Fault
Audible Alarms	On Battery, Low Battery, Overload
Software	PowerPanel® Personal Edition
PHYSICAL	
Form Factor	Compact
Keyhole Mounting Slots	Yes
Dimensions (WxHxD) (in.)	11 x 6.5 x 3.5
Weight (lbs.)	14.0
ENVIRONMENTAL	
Operating Temperature	32°F to 95°F / 0°C to 35°C
Operating Relative Humidity	0% - 95% non-condensing
CERTIFICATIONS	
Safety	UL1778, cUL 1071, FCC DOC Class B
Environmental	RoHS Compliant
WARRANTY	
Product Warranty	3 Years Limited
Connected Equipment Guarantee	Lifetime
CEG Amount	\$175,000